



NORMATIVE

Buoyant Orange Signals, approved in conformity to the last updating of the normative:

SOLAS 74 Directive 2014 / 90 / EU
UK MER: MERB00008R8
CE DIRECTIVE 2013 / 29 / EU

INSTRUCTIONS FOR USE

Remove the red lid. Pull the loop. Throw the signal overboard The case is made of corrosion-resistant steel

APPLICATIONS

For daylight distress signaling purposes on ship, lifeboats, life rafts and for pleasure craft.

DATA SHEET

ITEM N°	S.01
COMMERCIAL NAME	"BOETTA II" - Orange Smoke
MANUFACTURER	Albatross S.r.l V. Gramsci 13 - 80122 - ITALIA (Na)
COVERING	The case is made of corrosion-resistant steel
DIMENSIONS	Height 115 mm., Ø 75 mm.
WEIGHT	Gr. 390
BURNING TIME	> 3 min.
COLOR INTENSITY	Orange Smoke
ATTIVAZIONE	Manual
NEC	Gr. 190

Packing & Transport Information

- 25 Signals in fibreboard box Measurements of fibreboard box: 41 x 41 x 13
- Gross weight per pack 10.65 kg Net weight per pack 9.75 kg
- Net Explosive Content per box : 4.75 kg Hazard class 1.45 UN 0507
- Proper Shipping name: Signals, Smoke
- Other information: Cargo aircraft and Passenger

