



# HAND FLARE II

TECHNICAL DATA SHEET

## NORMATIVE

Hand Flare *red* light, approved in conformity to the last updating of the normative:

SOLAS 74 Directive 2014 / 90 / EU

UK MER: MERB00008R7

CE DIRECTIVE 2013 / 29 / U

## INSTRUCTIONS FOR USE

Hold the signals and *open* the lid. Pull the loop.

The flare ignites after 2 *sec.* delay.

Hold the signal upward, overboard and downwind

Tube is made of corrosion-resistant steel with a shockproof plastic handle.

## APPLICATIONS

For night - time distress signaling purposes on ships, lifeboats, life rafts and for pleasure craft.

## DATA SHEET

ITEM N°	S.02
COMMERCIAL NAME	"HAND FLARE II"
MANUFACTURER	Albatross S.r.l. - V. Gramsci 13 - 80122 - ITALIA (Na)
COVERING	Tube is made of corrosion-resistant steel
DIMENSIONS	Height 235 mm., Ø 25 mm.
WEIGHT	Gr. 200
BURNING TIME	> 60 sec
LIGHT INTENSITY	15.000 candele
ACTIVATION	Manual
NEC	Gr. 65

### Packing & Transport Information

- 60 Signals in fibreboard box
- Measurements of fibreboard box: 35 x 25 x 16
- Gross weight per pack 10.40 kg
- Net weight per pack 10.00 kg
- Net Explosive Content for box : 3.90 kg
- Hazard class 1.4G
- UN 0191
- Proper Shipping name Signal devices, Hand
- Other information: Cargo aircraft only

