



SHUTTLE

TECHNICAL DATA SHEET

NORMATIVE

Red light parachute rocket, The signal is approved in conformity to the last updatings of the normative:

SOLAS 74 Directive 2014 / 90 / EU
UK MER: MERB00008R6
CE DIRECTIVE 2013 / 29 / EU

INSTRUCTIONS FOR USE

- Remove bottom lid using the pin
- Release the trigger, positioning it outward. Grip the tube with both hands. Pushing the trigger against outer casing
- The launching tube is made of resistant plastic to ensure protection in severe marine weather conditions

APPLICATIONS

For nightlight distress signaling purposes on ship, lifeboats, life rafts and for pleasure craft.

DATA SHEET

ITEM N°	S.03
COMMERCIAL NAME	"SHUTTLE" • parachute rocket
MANUFACTURER	Albatross S.r.l. -V. Gramsci 13- 80122 - ITALY (Na)
COVERING	Tube of resistant plastic
DIMENSIONS	Height 261 mm., Ø 50 mm.
WEIGHT	Gr. 410
BURNING TIME	> 40 sec
LIGHT INTENSITY	RED : 30.000 candele
ACTIVATION	Manual
NEC	Gr. 150

Packing & Transport Information

- 21'2 Rockets in 2 metal tins in a fibreboard box
- Measurements of fibreboard box: 63 x 37 x 32
- Gross weight per pack 21.02 Kg • Net weight per pack 17.22 Kg
- Net Explosive Content per box : 6.30 Kg • Hazard class 1.4G • UN 0505
- Proper shipping name: SIGNALS, DISTRESS • Other information: Cargo aircraft only

